

# tesa® seal flex 60077, Flexible vapour barrier tape

Holder/Issued to

## tesa AB

Box 10275  
SE-434 23 Kungsbacka, Sverige  
Organisation number: SE556640031201  
Tel: +46 (0) 300-553 50  
E-mail: [cs.se@tesa.com](mailto:cs.se@tesa.com), Website: [www.tesa.com](http://www.tesa.com)

### Product description

tesa® seal flex 60077 is a reinforced, age resistant, low-density polyethylene (LDPE) tape with acrylate adhesive.

### Intended use

Construction tape intended for jointing of polyethylene water and vapor barriers and Bison wind protection layer (P-marked with approval number 0824/97).

### Trade name

tesa® seal flex 60077, Flexibel byggfolietejp

### Approval

The product has been found to meet the requirements in the following sections of Boverket Building Regulations (BBR) issued by the National Board of Housing, Building and Planning.

Moisture, General  
Air tightness

6:51, first sentence  
6:531

### Associated documents

Installation Instruction: "Monteringsanvisning tesa seal flex 60077", dated 9<sup>th</sup> October 2020 by RISE.

### Control

The factory production control (FPC) is monitored by an independent inspection body.  
Control agreement: 210-03-0207, Inspection body: RISE Research Institutes of Sweden AB.

When the building proprietor performs inspection at the building site, markings shall be checked to ensure that the correct products have been supplied and that they are used in accordance with the conditions in this approval and associated documents.

### Manufacturing place

Production control includes the following place/s:  
TESA SE, Norderstedt, Germany

Certificate no. C900179 | 2020-11-24

RISE Research Institutes of Sweden AB | Certification  
Box 857, SE-501 15 Borås, Sverige  
Tel: +46 10-516 50 00  
[certifiering@ri.se](mailto:certifiering@ri.se) | [www.ri.se](http://www.ri.se)

2019-06-10




(19495) 2P07019



## Marking

The product is to be marked at the factory. The marking consists of a label on every product supplied and includes:

Holder of certificate  
Manufacturing place  
Product type designation  
Length, Width  
Certificate number  
Consecutive manufacture No.  
P-mark  
Certification and Inspection body

tesa SE  
Norderstedt  
tesa® seal flex 60077  
value, value  
C900197  
No.  
  
RISE

## Basis for assessment/approval

Report 8F008593 Rev 1 and 8F019590 Rev 2 from RISE Research Institutes of Sweden AB.

## Comments

The tape shall be packed in such a way that it will not be exposed to UV radiation during storage. The durability of tesa® seal flex 60077, against the surface of air and vapour barriers (construction tape) and Bison wind protection layer (P-marked with approval number 0824/97), is deemed to be at least 50 years, if it is handled and applied in accordance with the associated documents.

## Validity

Valid through 8<sup>th</sup> October 2025.

Martin Tillander

*This is a translation from the Swedish original document. In the event of any dispute as to its content, the Swedish text shall take precedence.*

Certificate no. C900179 | 2020-11-24

**RISE Research Institutes of Sweden AB | Certification**