

DECLARATION OF PERFORMANCE

BB - Alupap

- Unique identification code of the product-type:
Alupap
- Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11 (4):
Alupap (stated on packaging or printing of the product)
- Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:
**Application: Flexible sheets for water proofing. Plastic and rubber control layers.
Vapor insulation material (paper coated with aluminum), used as vapor barrier for inner walls, floors or ceilings constructions. The product can be mounted directly onto the insulation material. There are no hazardous materials in it.**
- Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):
Baltijos Brasta Ltd., Palemono str. 7B, LT-52158 Kaunas
- Name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):
Not listed
- System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:
System 4
- In case of the declaration of performance concerning a construction product covered by a harmonized standard:
Not applicable
- In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
Not applicable
- Declared performance:
Harmonized technical specification EN 13984:2013

Essential characteristics			Performance		
Property	Method	Units	Nominal	Minimum	Maximum
Water vapour transmission (Sd)	EN 1931	m	200	-50	+50
Water tightness	EN 1928	Class	W1	-	-
Reaction to fire	EN ISO 11925-2	Class	F	-	-
Maximum tensile force (MD)	EN 12311-2	kN/m	5.2	-10%	+10%
Maximum tensile force (CMD)	EN 12311-2	kN/m	2.7	-10%	+10%
Elongation at max. Tensile force (MD)	EN 12311-2	%	1.8	-5%	+5%
Elongation at max. Tensile force (CMD)	EN 12311-2	%	16	-5%	+5%
Variation after artificial ageing:	EN 13859	Change			
Water tightness		Class	W1	-	-
Maximum tensile force (MD)		%	<20	-	-
Elongation at max. Tensile force (MD)		%	<20	-	-
Maximum tensile force (CMD)		%	<20	-	-
Elongation at max. Tensile force (CMD)		%	<20	-	-
Additional properties					
Mass per unit area	EN 1849	g/m ²	104	-6	+6
Length	EN 1848	m	30	-0,5%	+0,5%
Width	EN 1848	m	1,0 – 1.2	-0,5%	+0,5%

MD – machine dimension; CMD – cross machine dimension.

- The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Kaunas, 2013-07-01
Project manager

Saulius Pupius


