DECLARATION OF PERFORMANCE

NR 001/CD/STEELA/2019

1. Unique identification code of the product-type:

Grate elements for suspended ceilings - STEELA PROFIL, type CD 60

2. Intended application or applications:

Inside the buildings, installation of the grate of the suspended ceiling.

3. Manufacturer:

STEELA PROFIL Sp. j., ul. Dojazdowa 2A, 19-300 Ełk.

4. Authorized representative:

Not applicable

5. System or systems of assessment and verification of the constancy of the performance:

System 3

6a. Harmonised standard:

PN-EN 13964:2014-05 (EN 13964:2014)

Notified body or bodies:

BUILDING RESEARCH INSTITUTE, notification no. 1488 – has determined the product type on the ground of type examination (basing on samples collected for the examination by the manufacturer), has issued Examination Reports no. LZK00-00604/19/Z00NZK, LOW-679.1/P/2009, nr LOW01-0680/13/Z00OWN.

7. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Euroklass A1	
Bending class	Class 2	
Material	DX51D+Z100 up to Z275 g/sqm with thicknesses: 0,45 mm; 0,50 mm; 0,60 mm.	PN-EN 13964:2014-05 (EN 13964:2014)
Load capacity:		(LN 13904.2014)
thickness 0,45 mm	90 N (usable load)	
	248 N (destructive load)	
thickness 0,50 mm	105 N (usable load)	
	301 N (destructive load)	
thickness 0,60 mm	144 N (usable load)	
	461 N (destructive load)	
Suspension and fastening	NPD	
elements		

Upper anchorage mounting, fixing of wall sections	NPD	
Cross-section:	CD60	
dimensions	27,0 / 60 / 27,0 mm	PN-EN 13964:2014-05
tolerances	±0,3 / ±0,3 / ±0,3 mm	(EN 13964:2014)
Resistance to anchorage	NPD	
Durability	Class B	

The performance of the above qualified product complies with the range of the declared performance. The present declaration of performance is issued in accordance with the regulation (EU) no. 305/2011 on the sole responsibility of the above stated manufacturer.

For and on behalf of the manufacturer signed by:

URSZULA GRÓBARCZYK Wspólnik

Elk, 06.08.2019 r.