

NOBLE

TECHNICAL PRODUCT CARD

Feature	Standard	Unit	Result
			NOBLE with integrated underlay IXPE
Type	EN 649		Heterogeneous vinyl flooring
Pinnakaitse			ceramic
Surface			structural
Lock			5G
Usage class	EN 685	class	32/41
Total thickness	EN 428	mm	5.5
Wear layer thickness	EN 429	mm	0.5
Total weight	EN 430	g/m ²	9450
Wear group	EN 660-2	class	T
Residual inditation	ISO 24343-1:2007	mm	0,01
Dimensional stability	ISO2399:2008	%	width 0,08% , lenght 0,07%
Reaction to fire	EN 13501-1	class	B _f s ₁
Furniture leg	EN 425		Suitable for castor chair wheel type W
Underfloor heating	EN 12524		Suitable (subfloor temperature maximum max 27°C)
Thermal resistance	EN12667:2001	m ² K/W	0,038
Chemical resistance	ISO26987:2008		Not affected
Static Electrical property			yes
Formaldehyde emission			E1
Slip resistance	DIN51130		R10
	EN 13893	class	DS
Light fastness	EN 105-B02 Method 3		≥ 6
Format	EN 427	measure	198x1295mm
		box	2.05 m ²
		pallet	131.2 m ²

Imported by Lincona Konsult AS