

MODENA80_R_16W_LED_1140	IP44	IK03	○	CE	
-------------------------	------	------	---	----	--

**Tope article** 6004000019

**Data Sheet**

Surface/suspended edge lit LED luminaire with a slim 27mm profile. Electronic, fixed output gear. IP44 protection degree. IK03. Body: sheet aluminium white (RAL9016). Diffuser: UV-stabilised, PRO-LINE prismatic optic. Electrical connection via push wire terminal blocks. Complete with 4000K LED. With integrated driver.

Dimensions: Ø145x27 mm.

Total power: 15,3W

Luminaire luminous flux: 1168 lm

Luminaire efficiency: 76,34 lm/W

Weight: 1,0 kg

Light source: LED

Color rendering index min.: >80

Correlated colour temperature: 4000 Kelvin

Rated median useful life: 50000 L90 25°C

Ballast: 2xTUV

Luminaire input power: 16W

Dimming: Fixed output



All values are rated values. TopE Lighting uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Colour temperature is subject to a tolerance of up to +/-150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of 25°C. In most products the failure of one LED point causes no functional impairment to the lighting performance of the luminaire and is therefore no reason for complaint

